STATE OF NORTH DAKOTA

BOARD OF WATER WELL CONTRACTORS

900 E. BOULEVARD • BISMARCK, NORTH DAKOTA 58501

WELL DRILLER'S REPORT

State law requires that this report be filed with the State Board of Water Well Contractors within 30 days after completion or abandonment of the well.

1. WELL OWNER

Name: Tom Tessizk

Address: 4249 Hwy 85 S, Belfield ND

2. WELL LOCATION

Sketch map location must agree with written location.

NORTH

1 MILE

Sec. (1 mile) ____

County: STARK

NE 1/4 SE 1/4 ___ 1/4 Sec. 5 Twp. 138 N.Rg 99 W.

3. PROPOSED USE

☒ Domestic ☐ Stock ☐ Geothermal ☐ Irrigation ☐ Municipal ☐ Monitoring ☐ Industrial ☐ Test Hole

4. METHOD DRILLED

☐ Cable ☒ Forward Rotary ☐ Reverse Rotary ☐ Jetted ☐ Bored ☐ Auger

If other, specify ____

5. WATER QUALITY

Was a water sample collected for:

Chemcial Analysis? ☐ Yes ☒ No

Bacteriological Analysis? ☐ Yes ☒ No

If so, to what laboratory was it sent? ____

6. WELL CONSTRUCTION

Diameter of hole 8 3/4 inches. Depth 357 feet.

Casing: ☐ Steel ☒ Plastic ☐ Concrete ☐ Threaded ☐ Welded ☐ Other

If other, specify ____

Pipe Weight:	Diameter:	From:	To:
SDR17 250 lb/ft	5 inches	+1 feet	359 feet
____ lb/ft	____ inches	____ feet	____ feet
____ lb/ft	____ inches	____ feet	____ feet

Was perforated pipe used? ☐ Yes ☒ No

Perforated pipe set from ____ ft to ____ feet

Was casing left open end? ☐ Yes ☒ No

Was a well screened installed? ☒ Yes ☐ No

Material: Stainless Steel Diameter: 2 inches

Slot Size: 18 set from 360 feet to 386 feet

Slot Size: Blank 2" Riser set from 335 feet to 360 feet

Blank 2" Bottom 380 to 385

Was packer or seal used? ☐ Yes ☐ No

If so, what material: Bentonite Chips Depth: 357 ft.

(stainless steel, bronze, etc.)

Type of well: Straight screen ☐ Gravel packed ☒ Silica Sand #10

Depth grouted: From 0 To 45'

Grouting Material: Cement ____ Other ____

If other explain: Cement + Bentonite mix

Well head completion: Pitless unit ____

12" above grade ____ Other ____

If other, specify ____

Was pump installed: ☐ Yes ☒ No

Was well disinfected upon completion? ☒ Yes ☐ No

7. WATER LEVEL

Static water level 208 feet below surface

If flowing: closed-in pressure ____ psi

GPM flow ____ through ____ inch pipe

Controlled by: ☐ Valve ☐ Reducers ☐ Other

If other, specify ____

8. WELL TEST DATA

☐ Pump ☐ Bailer ☒ Other

Pumping level below land surface:

300	ft. after	3	hrs. pumping	10	gpm
____	ft. after	____	hrs. pumping	____	gpm
____	ft. after	____	hrs. pumping	____	gpm

9. WELL LOG

Formation	Depth (ft.) From	Depth (ft.) To
Clay Br.	0	16
Coal	16	26
Clay Gray	26	36
Rock	36	38
Clay	38	84
Coal	84	96
Clay	96	126
Rock	126	127
Clay	127	194
Rock	194	196
Clay	196	258
Rock	258	259
Clay	259	268
Coal	268	271
Clay	271	325
Coal	325	330
Clay Sandy Lt Blue	330	360
Sand Gray fine, Silt layers	360	380
Clay Lt Blue	380	392

(Use separate sheet if necessary)

10. DATE COMPLETED 5-30-98

11. WAS WELL PLUGGED OR ABANDONED?

☐ Yes ☒ No

If so, how ____

12. REMARKS:

13. DRILLER'S CERTIFICATION

This well was drilled under my jurisdiction and this report is true to the best of my knowledge.

J L Drilling — Driller's or Firm's Name

154 — Certificate No

940 North Ridge Drive #202 Dickinson ND — Address

Gerry Angney — Signed by

6-8-98 — Date

WHITE-DRILLER'S COPY YELLOW-BOARD'S COPY PINK-CUSTOMER'S COPY