



WELL DRILLER'S REPORT
NORTH DAKOTA BOARD OF WATER WELL CONTRACTORS
STATE OF NORTH DAKOTA
SFN 60273 (8/2023)

RECEIVED

FEB 07 2025

ND Board of Water Well Contractors • 1200 Memorial Highway • Bismarck, ND, 58504
State law requires that this report be filed with the State Board of Water Well Contractors within 30 days after completion or abandonment of the well.

ND DEPT. OF WATER RESOURCES

WELL OWNER				Was Pump Installed? ☐ Yes ☒ No			
Name Jay Obergewitch				Was Well Disinfected Upon Completion? ☐ Yes ☒ No			
Address Box 461 Beach, ND 58621				WATER LEVEL			
WELL LOCATION Sketch map location must agree with written location.				Static Water Level (In Feet) Below Surface 134			
		County Golden Valley		GPS		If Flowing, Closed-In Pressure In PSI	
		1/4 SW		1/4 SE		GPM Flow Through Inch Pipe	
Township 139N		Range 105E		Section 26		Controlled By ☐ Valve ☐ Reducers ☐ Other ☐ If Other, Specify _____	
PROPOSED USE 13910526DC				WELL TEST DATA			
☐ Domestic ☐ Geothermal ☐ Municipal ☐ Industrial ☒ Stock ☐ Irrigation ☐ Monitoring ☐ Test Hole				☒ Pump ☐ Bailer ☒ Other air			
METHOD DRILLED				Pumping Level Below Land Surface			
☐ Cable ☐ Jetted ☒ Forward Rotary ☐ Reverse Rotary ☐ Bored ☐ Auger ☐ If Other, Specify _____				Feet After Hrs. Pumping GPM			
WATER QUALITY Was a water sample collected for				172 4 12			
Chemical Analysis? ☐ Yes ☒ No				Feet After Hrs. Pumping GPM			
Bacteriological Analysis? ☐ Yes ☒ No				Feet After Hrs. Pumping GPM			
If So, To What Laboratory Was It Sent?				WELL LOG			
WELL CONSTRUCTION				Formation Depth (ft.)			
Diameter Of Hole In Inches 8"		Depth In Feet 280		From		To	
Casing: ☒ Steel ☒ Plastic ☐ Concrete ☐ Other ☐ Threaded ☐ Welded ☐ If Other, Specify _____				sand & scoria 0 34			
Pipe Weight	Diameter	From	To	gray clay 34 47			
28 lb/ft	8" inches	+2 feet	40 feet	coal 47 49			
SDR17	4.5 inches	0 feet	240 feet	gray clay 49 110			
				gray sand 110 117			
				gray clay 117 140			
				gray sand 140 182			
				gray clay 182 194			
				rock 194 198			
				gray clay 198 236			
				gray sand 236 272			
				gray shale 272 280			
Was A Well Screen Installed? ☒ Yes ☐ No							
Was Perforated Pipe Used? ☐ Yes ☒ No							
Screen Or Perforation Interval continuous		From In Feet 240	To In Feet 280				
Was Casing Left Open End? ☒ Yes ☐ No							
Material PVC		Diameter In Inches 4.5		Use Separate Sheet If Necessary			
Slot Size .025	Set From In Feet 240	To In Feet 280		DATE COMPLETED 8-1-24			
Was Packer Or Seal Used? ☒ Yes ☐ No				WAS WELL PLUGGED OR ABANDONED? ☐ Yes ☐ No			
If So, What Material 1/4" pea gravel		Depth In Feet 230-280		If So, How			
Type Of Well ☐ Straight Screen ☐ Gravel Packed				REMARKS			
Depth Grouted 230	From 0	To 230					
Grouting Material Bentonite		Cement					
If Other, Explain:							
Well Head Completion: Pitless Unit				DRILLER'S CERTIFICATION			
12" Above Grade X		Other (Specify)		This well was drilled under my jurisdiction and this report is true to the best of my knowledge.			
If Other, Specify				Driller's Or Firm's Name H&H Drilling		Certificate Number 162	
				Address 109 west river road lane Glendive, Mt 59330			
				Signed By Mike Haggerty		Date 8-26-24	